

# TECHNICAL DATA SHEET


## Adhesive lubricant HHS® 200 PLUS

Art. no. 0893 106 204

P. Qty.: 1 / 12

### High-performance lubricating grease for extreme loads

Chemical basis	Synthesis of fat and additives in hydrocarbon solvents
Oil basis	Fat synthesis
Colour	Beige
Smell/fragrance	Characteristic
Density	0.795 g/ml
Min. temperature conditions	-40 °C
Max. temperature conditions	180 °C
Max. temperature resistance	1000 °C
Min. flashing point of active ingredient	200 °C
Min. flashing point	200 °C
Kinematic oil basis viscosity	1000 cSt
Conditions for viscosity of oil basis	at 40°C
Silicone-free	Yes
Acid-free	Yes
Resin-free	Yes
Resistance against	Water, Salt water, Weak lyes, Weak acids
Material compatibility	Steel, Non-ferrous heavy metals, Stainless steel, EPDM, FKM, NBR
Contents	400 ml
Weight of content	248 g
Shelf life from production	24 Month
Sustainability	Pollutants/Emissions



### Application area

For professional lubrication under extremely high pressure loads and/or the influence of weather and water such as open gears and chains, even in outdoor applications.

# TECHNICAL DATA SHEET

## Proof of Performance



## Notice

Physiologically safe lubricant; ideally suited for the food processing industry. NSF H1-registered.

The application instructions are recommendations based on the tests we have conducted and on our experience; please carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. If our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.