

TECHNICAL DATA SHEET

Maintenance oil Multi

Art. no. 0893 055 40

P. Qty.: 1 / 12

Versatile multi-functional spray for a range of applications

- Loosens rust with excellent corrosion penetration
- Excellent lubricating properties
- Effective cleaning guaranteed
- Ideal corrosion protection prevents moisture from collecting in even the smallest surface imperfections
- Resolves leakage current
- Resin, acid, and silicone-free
- Does not attack rubber, paint or plastics



Contents	0.4 l
Chemical basis	Mineral oil
Colour	Light yellow transparent
Min./max. processing temperature for can	-10 to 40 °C
Min./max. temperature conditions	-30 to 130 °C
Shelf life from production	24 Month
Min. processing temperature for can	-10 °C
Type of spray head	Standard spray head
Max. processing temperature for can	40 °C
Min. temperature conditions	-30 °C
Max. temperature conditions	130 °C
Min. flashing point	-80 °C
Silicone-free	Yes
Acid-free	Yes
Resin-free	Yes
AOX-free	Yes
White oil-free/mineral oil-free	No
VOC concentration (CH)	76.57 g/l
Kinematic oil basis viscosity	30 cSt
Material compatibility	Steel, Non-ferrous heavy metals, Stainless steel, Epoxy glass fabric, EPDM, FKM, PE, PP, Vinyl, PTFE, PL, PA, NBR
Conditions for viscosity of oil basis	at 40 °C
Container	Aerosol can
Weight of content	270 g
Conditions to maintain shelf life from production	at 20 °C

TECHNICAL DATA SHEET

Application area

Versatile multi-purpose spray

Application information

Used for releasing rusted bolts, pipe fittings, screws, nuts, joints, Bowden cables, shafts, locks, etc. Lubricates locks, hinges, sleeves, chains, and door closers. Stops squeaking and creaking. Cleans and protects plastic and metal parts, e.g. panels and housings. Prevents corrosion of metals and electrical assemblies, cable connections, relays, plugs, couplings, etc. Prevents the freezing of lock cylinders and closures. Penetrates and displaces moisture in electrical assemblies. Used for releasing rusted bolts, pipe fittings, screws, nuts, joints, Bowden cables, shafts, locks, etc. Lubricates locks, hinges, sleeves, chains, and door closers. Stops squeaking and creaking. Cleans and protects plastic and metal parts, e.g. panels and housings. Prevents corrosion of metals and electrical assemblies, cable connections, relays, plugs, couplings, etc. Prevents the freezing of lock cylinders and closures. Penetrates and displaces moisture around electrical and electronic systems. Shake the can before use, spray the parts and let it take effect briefly. After using, spray the can upside down until it is empty.

The usage instructions are recommendations based on the tests we have conducted and our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.