

# TECHNICAL DATASHEET

**0893 113 114**

## **Zinc spray, light**

Long-term protection and repair of metallic surfaces.

### **Application areas:**

Steel construction, shipbuilding, forging, fitter's shops and vehicle construction, etc.

### **Properties:**

- Cold galvanising
- Protects against rust
- Abrasion-resistant
- Spot weldable
- Good adhesive properties on bare metal

### **Application:**

The zinc spray is suitable for repairing machining damage and rust spots on zinc plated parts. It has an excellent metal primer.

### **Technical data:**

Colour	Zinc, bright
Contents	400 ml
Temperature resistance	to approx. +240 °C
Flash point	below +21 °C
Min. curing time	10 hours
Max. curing time	12 hours
Dust-dry time	15 min
Dry layer thickness	30 µm

### **Notes:**

Store in a dry place and at room temperature (15–25 °C), minimum shelf life of 30 months.

Not suitable as primer for PU, MS polymer or hybrid sealing compounds.

# TECHNICAL DATASHEET

We provide this advice based on our own tests and experience and to the best of our knowledge. However, due to the large number of applications and the storage and handling conditions that lie outside the scope of our influence, we assume no liability for the application results in individual cases.

This also applies to the use of the non-binding technical and commercial customer service provided by us. We always recommend that you conduct your own tests. We guarantee the consistent quality of our products. We reserve the right to make technical changes and further develop products.